



Application Instructions for  
Colour Print Extra

Heat seal material, specifically formulated for ink jet solvent and eco solvent based inks – print and cut systems.

Accessories Required: Release paper and Colour Print Mask.

Colour Print Extra is a high opacity material; a very thin digital media that is incredibly soft to the hand.

It has an adhesive polyester backing and is suitable for non-coated fabrics such as nylon jackets, sportswear, bags, umbrellas and leather

Application instructions:

1. Print and cut the material and allow to dry for 8 – 12 Hours
2. Weed the material
3. Remove the image from the backer using Colour Print Mask
4. Cover with Release Paper and Heat Apply as follows:

Temperature: 165°C  
Time: 12 - 14 seconds  
Pressure: Minimum

5. Peel the Colour Print Mask while HOT.

**DO NOT STRETCH IMMEDIATELY AFTER HEAT APPLYING.**

**Washing Instructions:** Wait 24 hours after heat pressing.

Machine-wash inside out at 30°C using a mild detergent. Do not bleach. Iron in reverse – do not iron over.

*All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance under conditions not under manufacturer's control. Before using, please determine suitability of product for its intended use. I.e, do your own wash test.*

*Warranty of product is to replace product only and not the item this has been applied to.*

*Using transfer paper may invalidate printer warranty please check with printer manufacturer or supplier.*