

	<p>Application Instructions for Colour Print Protect</p>
	<p>Recommended Fabrics: (Depending on Material)</p> <ul style="list-style-type: none"> • Cotton, • Polyester, • Poly-cotton blends, • Nylon • Silicon treated garments. <p>Not suitable for dyed garments (sublimation inks)</p>

Description:

Colour Print Protect film can be applied on some of Target’s Printable Media, printed with eco solvent based inks, to protect from abrasion and discolouration:

Basic Information:

For the correct application of the film on printed products, transfer conditions are indicated on the following table:

Product	Transfer of printed product	Application of Colour Print Protect	Glossy finish	Maximum washing Temperature
Colour Print Classic	175°C for 3 seconds Medium Pressure	175°C for 30 seconds Medium Pressure	175°C for 5-10 seconds Medium Pressure	90°C
Colour Print Extra	175°C for 3 seconds Low Pressure	175°C for 30 seconds Low Pressure	175°C for 5-10 seconds Low Pressure	40°C
Colour Print Quick	175°C for 3 seconds Medium Pressure	175°C for 30 seconds Medium Pressure	175°C for 5-10 seconds Medium Pressure	60°C

Application Instructions:

- I. Print the digital product (among those indicated in the table above) following the instructions stated on their product information sheet.
- II. Heat apply the print as instructed in the above table.
- III. Hot peel the print once applied.
- IV. Overlay the protective film on the print with the paper backing facing up.
- V. Heat apply as instructed on in the above table.
- VI. Remove the paper backing and cold peel only.
- VII. In order to obtain a glossy finish, press again, overlaying with silicon cover sheet, as instructed in the above table.

Washing Instructions:

Compatible with the fabric used, follow the instructions in the above table.

Do not use bleach or other aggressive chemical agents.

DO NOT DRY CLEAN OR TUMBLE DRY

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance under conditions not under manufacturer’s control. Before using, please determine suitability of product for its intended use. ie, do your own wash test.

Warranty of product is to replace product only and not the item the transfer has been applied to